


Lux Brush/Carpet - open

Code: TOBC





EMPIRE is an optimal, wider and modern aludoormat, with double inlay. Imagine your impressive entrance with Empire STILMAT doormat. Extra wide for all buildings, with high demands with regard to resilience and harmonious appearance. Suitable for internal use and for normal to heavy frequency of passengers. This model is with thorough brushes for extra cleaning effect and high quality dust control carpet. Ideal for picking up coarse dirt, fine dirt and moisture. Anodized aluminum doormat model with 24 mm height. The weather-proof solution among the robust solution.




The weather-proof solution

Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys

Ideal for: Coarse dirt, fine dirt and moisture

Aluminum coating: Fully anodized

Logo options: Logo engraving





STILMAT EMPIRE

Lux Brush/Carpet - open

Code: TOBC

Model	Empire (Lux brush & Carpet)
Tread surface (inlay):	Lux brushes recessed, robust and high quality dust control carpet, durable and luxurious character. Made from 100% Polyamide. Weather-proof
Ideal for:	Coarse dirt, fine dirt and moisture
Colors:	Black, Grey, Brown
Version	Open system
Code	TOBC
Approx. height (mm)	24
Entrance position	Covered outdoor areas, gateways, passages
Zones: I – II - III	Zone: II
Load	Heavy
Footfall	Daily footfall up to 2000
Roll-over and drive-over capability:	Wheelchairs, Prams, Hand and Light shopping trolleys
Support chassis	Made from rigid anodized aluminum with rubber sound insulation underlay
Aluminum coating:	Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.
Aluminum material thickness (mm)	1.2
Connection	Strong and flexible PVC connection strip, the entire width
Standard profile clearance approx. (mm)	5 mm (optional 3mm for automatic/revolving doors)
Slip resistance	Brush R13 - Carpet DS
Max width/profile length for each individual section (mm):	6000
Max depth/walking depth for individual units (mm):	Any
Mat divisions as per factory standards or customer specifications	Recommended maximum mat weight of 45 kg
Depth for individual units (mm):	Cca 24
Stationary load kg/100cm²	2200
Weight (kg/m²)	Cca 17
Logo options	Logo engraving
Contact	STILMAT

Garancija: 5 godina na aluminijumske delove i konstrukciju

