



ZONE



HEIGHT (mm)



STILMAT PRINZ

Rubber - closed

Code: JCR



PRINZ is famous and the lowest model of STILMAT alu doormats. The alternative system with closed design. Ideal for small pit depth for picking up fine dirt and moisture. Anodized aluminum doormat model with 12mm height and high quality dust control carpet. The weather-proof solution for entrances with normal to heavy visitor frequency. Imagine your impressive entrance with PRINZ STILMAT doormat. Suitable for internal use. Closed, hard-wearing entrance mats produced to fit width and walking depth specifications perfectly.



Ideal for: Coarse dirt, fine dirt and moisture



The weather-proof solution



Roll-over and drive-over capability: Wheelchairs,



Prams, Hand and Light shopping trolleys



Aluminum coating: Fully anodized
Logo options: Logo engraving



STILMAT PRINZ

Rubber - closed

Code: JCR

| Model | PRINZ (Rubber) |
|---|--|
| Tread surface (inlay): | Profiled rubber inserts. Weather-proof |
| Ideal for | Coarse dirt |
| Colors: | Black, Grey, Brown... |
| Version | Closed system |
| Code | JCR |
| Approx. height (mm) | 14 |
| Entrance position | Outdoors |
| Zones: I – II - III | Zone: I |
| Load | Heavy |
| Footfall | Daily footfall up to 1000 |
| Roll-over and drive-over capability: | Wheelchairs, Prams, Hand and Light shopping trolleys |
| Support chassis | Made from rigid anodized aluminum with rubber sound insulation underlay |
| Aluminum coating | Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum |
| Aluminum material thickness (mm) | 1.2 |
| Connection | Strong PVC connection strip, the entire width |
| Standard profile clearance approx. (mm) | 0 mm, closed system |
| Slip resistance | R12 wet, R13 dry |
| Max width/profile length for each individual section (mm): | 6000 |
| Max depth/walking depth for individual units (mm): | Any |
| Mat divisions as per factory standards or customer specifications | Recommended maximum mat weight of 45 kg |
| Depth for individual units (mm): | Cca 14 |
| Stationary load kg/100cm ² | 1650 |
| Weight (kg/m ²) | Cca 17 |
| Logo options | Logo engraving, rubber logo, LED logo |
| Contact | STILMAT |

Guarantee: 5 years on aluminum parts and construction