




ZONE




HEIGHT (mm)



STILMAT PRINZ

Rubber - open

Code: JOR



PRINZ is famous and the lowest model of STILMAT alu doormats. Ideal for small pit depth for picking up coarse dirt. Anodized aluminum doormat model which is only 14mm high, with profiled rubber inserts. The weather-proof solution for buildings with normal to heavy visitor frequency. Imagine your impressive entrance with PRINZ STILMAT doormat. Suitable for external use. Flexible and roll-up, entrance mats produced to fit width and walking depth specifications perfectly. Suitable for wheeled traffic. Any geometric shape is available on demand.



Ideal for: Coarse dirt, fine dirt and moisture



The weather-proof solution




Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys



Aluminum coating: Fully anodized



Logo options: Logo engraving



STILMAT PRINZ

Rubber - open

Code: JOR

Model	PRINZ (Rubber)
Tread surface (inlay):	Profiled rubber inserts. Weather-proof
Ideal for	Coarse dirt
Colors:	Black, Grey, Brown...
Version	Open system
Code	JOR
Approx. height (mm)	14
Entrance position	Outdoors
Zones: I – II - III	Zone: I
Load	Heavy
Footfall	Daily footfall up to 1000
Roll-over and drive-over capability:	Wheelchairs, Prams, Hand and Light shopping trolleys
Support chassis	Made from rigid anodized aluminum with rubber sound insulation underlay
Aluminum coating	Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum
Aluminum material thickness (mm)	1.2
Connection	Strong and flexible PVC connection strip, the entire width
Standard profile clearance approx. (mm)	5 mm (or 3mm for automatic/revolving doors)
Slip resistance	R12 wet, R13 dry
Max width/profile length for each individual section (mm):	6000
Max depth/walking depth for individual units (mm):	Any
Mat divisions as per factory standards or customer specifications	Recommended maximum mat weight of 45 kg
Depth for individual units (mm):	Cca 14
Stationary load kg/100cm ²	1650
Weight (kg/m ²)	Cca 14
Logo options	Logo engraving, rubber logo, LED logo
Contact	STILMAT

Guarantee: 5 years on aluminum parts and construction