

STILMAT BARON

Rubber - open

Code: BOR

Description:	Flexible and roll-up, aluminum entrance mat for laying on the floor. Custom produced mats to fit width and walking depth specifications perfectly. Suitable for wheeled traffic. Any geometric shape is available on demand.
Model	BARON (Rubber)
Tread surface (inlay):	Profiled rubber inserts
Ideal for:	Coarse dirt
Colors:	Black, Grey, Brown...
Version	Open system
Code	BOR
Approx. height (mm)	28 mm
Entrance position	Outdoors
Zones: I – II - III	Zone: I
Load	Extreme
Footfall	Daily footfall of 5000 and up
Roll-over and drive-over capability:	Wheelchairs, Prams, Hand and Light shopping trolleys
Support chassis	Made from rigid anodized aluminum with rubber sound insulation underlay
Aluminum coating:	Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.
Aluminum material thickness (mm)	1.2
Connection	Strong PVC connection strip, the entire width
Standard profile clearance approx. (mm)	5 mm (optional 3mm for automatic/revolving doors)
Slip resistance	R12 wet, R13 dry
Logo options	Logo engraving, rubber logo, LED logo
Contact	STILMAT

Guarantee: 5 years on aluminum parts and construction