## **STILMAT IMPERATOR**

Lux Brush/Rubber - open

Code: NPOBR

Model     IMPERATOR (Lux brush & Rubber)       Tread surface (inlay):     Special scraper bar mounted between profiles, Lux brushes recessed, robust and profiled rubber inserts       Ideal for     Coarse dirt       Colors:     Black, Grey, Brown       Version     Open system       Code     NPOBR       Approx. height (mm)     24 mm       Entrance position     Outdoors       Zones: I – II - III     Zone: I       Load     Extreme       Automatic door systems     Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005       Footfall     Daily footfall of 2000 and up       Roll-over and drive-over capability:     Wheelchairs, Prams, Hand and Light shopping trolleys       Support chassis     Made from rigid anodized aluminum with rubber sound insulation underlay       Aluminum coating:     Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.       Aluminum material thickness (mm)     1.2       Connection     Galvanized steel cable and rubber spacers       Standard profile clearance approx. (mm)     5 mm (or 3mm for automatic/revolving doors)       Slip resistance     Brush R13 - Rubber R12 wet, R13 dry       Logo options     Logo engraving       Contact     STILMAT	Decription	Flexible roll-up, extremely hard-wearing entrance mats produced to fit width and walking depth specifications perfectly. Suitable for wheeled traffic. Any geometric shape is available. STILMAT guarantee a custom spotless introduction to every entrance, because it is a synonym for aluminum doormats, modern and traditional glamour for every entrance and unique workman shift.
robust and profiled rubber inserts  Ideal for Coarse dirt  Colors: Black, Grey, Brown  Version Open system  Code NPOBR  Approx. height (mm) 24 mm  Entrance position Outdoors  Zones: I – II - III Zone: I  Load Extreme  Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005  Footfall Daily footfall of 2000 and up  Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys  Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay  Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm) 1.2  Connection Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors)  Slip resistance Brush R13 - Rubber R12 wet, R13 dry  Logo options	Model	IMPERATOR (Lux brush & Rubber)
Colors:  Black, Grey, Brown  Version  Open system  Code  NPOBR  Approx. height (mm)  24 mm  Entrance position  Outdoors  Zones: I – II - III  Load  Extreme  Automatic door systems  Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005  Footfall  Poally footfall of 2000 and up  Roll-over and drive-over capability:  Wheelchairs, Prams, Hand and Light shopping trolleys  Support chassis  Made from rigid anodized aluminum with rubber sound insulation underlay  Aluminum coating:  Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  1.2  Connection  Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  5 mm (or 3mm for automatic/revolving doors)  Slip resistance  Brush R13 - Rubber R12 wet, R13 dry  Logo options	Tread surface (inlay):	
Version Code NPOBR Approx. height (mm) 24 mm Entrance position Outdoors Zones: I – II – III Load Extreme Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Daily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) Sip resistance Brush R13 - Rubber R12 wet, R13 dry Logo options Logo engraving	Ideal for	Coarse dirt
Code Approx. height (mm) 24 mm Entrance position Outdoors Zones: I - II - III Load Extreme Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Daily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Brush R13 - Rubber R12 wet, R13 dry Logo options	Colors:	Black, Grey, Brown
Approx. height (mm)  Entrance position  Zones: I - II - III  Load  Extreme  Automatic door systems  Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005  Footfall  Paily footfall of 2000 and up  Roll-over and drive-over capability:  Wheelchairs, Prams, Hand and Light shopping trolleys  Support chassis  Made from rigid anodized aluminum with rubber sound insulation underlay  Aluminum coating:  Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  1.2  Connection  Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  5 mm (or 3mm for automatic/revolving doors)  Slip resistance  Brush R13 - Rubber R12 wet, R13 dry  Logo options	Version	Open system
Entrance position  Zones: I - II - III  Load  Extreme  Automatic door systems  Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005  Footfall  Poaily footfall of 2000 and up  Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys  Support chassis  Made from rigid anodized aluminum with rubber sound insulation underlay  Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  1.2  Connection  Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  5 mm (or 3mm for automatic/revolving doors)  Slip resistance  Brush R13 - Rubber R12 wet, R13 dry  Logo options	Code	NPOBR
Zones: I – II - III  Load  Extreme  Automatic door systems  Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005  Footfall  Paily footfall of 2000 and up  Roll-over and drive-over capability:  Wheelchairs, Prams, Hand and Light shopping trolleys  Support chassis  Made from rigid anodized aluminum with rubber sound insulation underlay  Aluminum coating:  Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  1.2  Connection  Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  5 mm (or 3mm for automatic/revolving doors)  Slip resistance  Brush R13 - Rubber R12 wet, R13 dry  Logo options	Approx. height (mm)	24 mm
Load Extreme  Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005  Footfall Daily footfall of 2000 and up  Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys  Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay  Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  1.2  Connection Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  5 mm (or 3mm for automatic/revolving doors)  Slip resistance Brush R13 - Rubber R12 wet, R13 dry  Logo options	Entrance position	Outdoors
Automatic door systems  Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005  Footfall  Roll-over and drive-over capability:  Wheelchairs, Prams, Hand and Light shopping trolleys  Support chassis  Made from rigid anodized aluminum with rubber sound insulation underlay  Aluminum coating:  Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  Connection  Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  Sippresistance  Brush R13 - Rubber R12 wet, R13 dry  Logo options  Logo engraving	Zones: I - II - III	Zone: I
accordance with EN 16005  Footfall  Daily footfall of 2000 and up  Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys  Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay  Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  1.2  Connection Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  5 mm (or 3mm for automatic/revolving doors)  Slip resistance Brush R13 - Rubber R12 wet, R13 dry  Logo options  Logo engraving	Load	Extreme
Roll-over and drive-over capability:  Support chassis  Made from rigid anodized aluminum with rubber sound insulation underlay  Aluminum coating:  Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  Connection  Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  Slip resistance  Brush R13 - Rubber R12 wet, R13 dry  Logo options  Logo engraving	Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN $16005$
Support chassis  Aluminum coating:  Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  Connection  Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  Slip resistance  Brush R13 - Rubber R12 wet, R13 dry  Logo options  Made from rigid anodized aluminum with rubber sound insulation underlay  Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  5 mm (or 3mm for automatic/revolving doors)  Logo engraving	Footfall	Daily footfall of 2000 and up
Aluminum coating:  Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  Connection  Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  5 mm (or 3mm for automatic/revolving doors)  Slip resistance  Brush R13 - Rubber R12 wet, R13 dry  Logo options  Logo engraving	Roll-over and drive-over capability:	Wheelchairs, Prams, Hand and Light shopping trolleys
aesthetically pleasing finish and harder surface than pure aluminum.  Aluminum material thickness (mm)  1.2  Connection  Galvanized steel cable and rubber spacers  Standard profile clearance approx. (mm)  5 mm (or 3mm for automatic/revolving doors)  Slip resistance  Brush R13 - Rubber R12 wet, R13 dry  Logo options  Logo engraving	Support chassis	Made from rigid anodized aluminum with rubber sound insulation underlay
Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Brush R13 - Rubber R12 wet, R13 dry Logo options Logo engraving	Aluminum coating:	
Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors)  Slip resistance Brush R13 - Rubber R12 wet, R13 dry  Logo options Logo engraving	Aluminum material thickness (mm)	1.2
Slip resistance Brush R13 - Rubber R12 wet, R13 dry Logo options Logo engraving	Connection	Galvanized steel cable and rubber spacers
Logo options  Logo engraving	Standard profile clearance approx. (mm)	5 mm (or 3mm for automatic/revolving doors)
	Slip resistance	Brush R13 - Rubber R12 wet, R13 dry
Contact	Logo options	Logo engraving
	Contact	STILMAT

Guarantee: 5 years on aluminum parts and construction