STILMAT IMPERATOR

Lux Brush/Ribbed carpet - open

Code: NPOBL

| ModelIMPERATOR (Lux brush & Ribbed carpet)Tread surface (inlay):Special scraper bar mounted between profiles, Lux brushes recessed, robust and High quality ribbed carpet for Public buildings (A+EFL), durable and luxurious character. Made from 100% Polyamide with gel backing. Weather-proofIdeal forCoarse dirt, fine dirt and moistureColors:Black, Grey, BrownVersionOpen systemCodeNPOBLApprox. height (mm)24 mmEntrance positionCovered outdoor areas, gateways, passagesZones: I - II - IIIZone: IILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleaing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engravingContactSTILMAT | Description: | Flexible and roll-up, aluminum entrance mat for laying on the floor. Custom produced mats to fit width and walking depth specifications perfectly. Suitable for wheeled traffic. Any geometric shape is available on demand. |
|--|---|---|
| robust and High quality ribbed carpet for Public buildings (A+EFL) , durable and luxurious character. Made from 100% Polyamide with gel backing. Weather-proofIdeal forCoarse dirt, fine dirt and moistureColors:Black, Grey, BrownVersionOpen systemCodeNPOBLApprox. height (mm)24 mmEntrance positionCovered outdoor areas, gateways, passagesZones: I - II - IIIZone: IILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Model | IMPERATOR (Lux brush & Ribbed carpet) |
| Colors:Black, Grey, BrownVersionOpen systemCodeNPOBLApprox. height (mm)24 mmEntrance positionCovered outdoor areas, gateways, passagesZones: I - II - IIIZone: IILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Tread surface (inlay): | robust and High quality ribbed carpet for Public buildings (A+EFL) , durable and luxurious character. Made from 100% Polyamide with gel backing. |
| VersionOpen systemCodeNPOBLApprox. height (mm)24 mmEntrance positionCovered outdoor areas, gateways, passagesZones: I - II - IIIZone: IILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Ideal for | Coarse dirt, fine dirt and moisture |
| CodeNPOBLApprox. height (mm)24 mmEntrance positionCovered outdoor areas, gateways, passagesZones: I - II - IIIZone: IILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Colors: | Black, Grey, Brown |
| Approx. height (mm)24 mmEntrance positionCovered outdoor areas, gateways, passagesZones: I - II - IIIZone: IILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Version | Open system |
| Entrance positionCovered outdoor areas, gateways, passagesZones: I - II - IIIZone: IILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Code | NPOBL |
| Zones: I – II - IIIZone: IILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Approx. height (mm) | 24 mm |
| LoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Entrance position | Covered outdoor areas, gateways, passages |
| Automatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Zones: I – II - III | Zone: II |
| accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Load | Extreme |
| Roll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Automatic door systems | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 |
| Support chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Footfall | Daily footfall of 2000 and up |
| Aluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Roll-over and drive-over capability: | Wheelchairs, Prams, Hand and Light shopping trolleys |
| Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Support chassis | Made from rigid anodized aluminum with rubber sound insulation underlay |
| ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Aluminum coating: | |
| Standard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Aluminum material thickness (mm) | 1.2 |
| Slip resistanceBrush R13 - Ribbed carpet DSLogo optionsLogo engraving | Connection | Galvanized steel cable and rubber spacers |
| Logo options Logo engraving | Standard profile clearance approx. (mm) | 5 mm (or 3mm for automatic/revolving doors) |
| | Slip resistance | Brush R13 - Ribbed carpet DS |
| Contact STILMAT | Logo options | Logo engraving |
| | Contact | STILMAT |

Guarantee: 5 years on aluminum parts and construction