STILMAT IMPERATOR

Rubber/Ribbed carpet - open

Code: NPORL

| ModelIMPERATOR (Rubber & Ribbed carpet)Tread surface (inlay):Special scraper bar mounted between profiles, profiled rubber inserts and High quality ribbed carpet for Public buildings (A+EFL), durable and luxurious character. Made from 100% Polyamide with gel backing. Weather-proofIdeal forCoarse dirt, fine dirt and moistureColors:Black, Grey, BrownVersionOpen systemCodeNPORLApprox. height (mm)22 mmEntrance positionCovered outdoor areas, gateways, passagesZones: I – II – IIIZone: IILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceRubber R12 wet, R13 dry - Ribbed carpet DSLogo optionsLogo engravingContactSTILMAT | Description: | Flexible and roll-up, aluminum entrance mat for laying on the floor. Custom produced mats to fit width and walking depth specifications perfectly. Suitable for wheeled traffic. Any geometric shape is available on demand. |
|--|---|---|
| and High quality ribbed carpet for Public buildings (A+EFL), durable and luxurious character. Made from 100% Polyamide with gel backing. Weather-proof Ideal for Coarse dirt, fine dirt and moisture Colors: Black, Grey, Brown Version Open system Code NPORL Approx. height (mm) 22 mm Entrance position Covered outdoor areas, gateways, passages Zones: I – II – III Zone: II Load Extreme Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Daily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options Logo engraving | Model | IMPERATOR (Rubber & Ribbed carpet) |
| Colors: Black, Grey, Brown Version Open system Code NPORL Approx. height (mm) 22 mm Entrance position Covered outdoor areas, gateways, passages Zones: I – II - III Load Extreme Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Daily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options | Tread surface (inlay): | and High quality ribbed carpet for Public buildings (A+EFL), durable and luxurious character. Made from 100% Polyamide with gel backing. Weather- |
| Version Code NPORL Approx. height (mm) 22 mm Entrance position Covered outdoor areas, gateways, passages Zones: I – II - III Load Extreme Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Daily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) Sip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options Logo engraving | Ideal for | Coarse dirt, fine dirt and moisture |
| Code NPORL Approx. height (mm) 22 mm Entrance position Covered outdoor areas, gateways, passages Zones: I - II - III Zone: II Load Extreme Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Daily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options | Colors: | Black, Grey, Brown |
| Approx. height (mm) Entrance position Covered outdoor areas, gateways, passages Zones: I – II - III Load Extreme Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Daily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) Sim (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options | Version | Open system |
| Entrance position Zones: I - II - III Load Extreme Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Poaily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options | Code | NPORL |
| Zones: I – II - III Load Extreme Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Daily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options | Approx. height (mm) | 22 mm |
| Load Extreme Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Daily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options | Entrance position | Covered outdoor areas, gateways, passages |
| Automatic door systems Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 Footfall Poily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options Logo engraving | Zones: I - II - III | Zone: II |
| accordance with EN 16005 Footfall Daily footfall of 2000 and up Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options Logo engraving | Load | Extreme |
| Roll-over and drive-over capability: Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) Simple from rigid anodized aluminum with rubber sound insulation underlay Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) Simple from rigid anodized aluminum with rubber sound insulation underlay Made from rigid anodized aluminum with rubber sound insulation underlay Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Logo options Logo engraving | Automatic door systems | |
| Support chassis Made from rigid anodized aluminum with rubber sound insulation underlay Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options Logo engraving | Footfall | Daily footfall of 2000 and up |
| Aluminum coating: Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options Logo engraving | Roll-over and drive-over capability: | Wheelchairs, Prams, Hand and Light shopping trolleys |
| aesthetically pleasing finish and harder surface than pure aluminum. Aluminum material thickness (mm) 1.2 Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options Logo engraving | Support chassis | Made from rigid anodized aluminum with rubber sound insulation underlay |
| Connection Galvanized steel cable and rubber spacers Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options Logo engraving | Aluminum coating: | |
| Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options Logo engraving | Aluminum material thickness (mm) | 1.2 |
| Slip resistance Rubber R12 wet, R13 dry - Ribbed carpet DS Logo options Logo engraving | Connection | Galvanized steel cable and rubber spacers |
| Logo options Logo engraving | Standard profile clearance approx. (mm) | 5 mm (or 3mm for automatic/revolving doors) |
| | Slip resistance | Rubber R12 wet, R13 dry - Ribbed carpet DS |
| Contact | Logo options | Logo engraving |
| | Contact | STILMAT |

Guarantee: 5 years on aluminum parts and construction