STILMAT KING

Lux Brush - open

Code: NOB

ModelKING (Lux Brush)Tread surface (inlay):Lux brushes recessed, robustIdeal for:Coarse dirtColors:Black, GreyVersionOpen systemCodeNOBApprox. height (mm)24 mmEntrance positionOutdoorsZones: I - II - IIIZone: ILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysAluminum noating:Full y anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engravingContactSTILMAT	Description:	Flexible and roll-up, aluminum entrance mat for laying on the floor. Custom produced mats to fit width and walking depth specifications perfectly. Suitable for wheeled traffic. Any geometric shape is available on demand.
Ideal for:Coarse dirtColors:Black, GreyVersionOpen systemCodeNOBApprox. height (mm)24 mmEntrance positionOutdoorsZones: 1 – II - IIIZone: 1LoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)Smm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Model	KING (Lux Brush)
Colors:Black, GreyVersionOpen systemCodeNOBApprox. height (mm)24 mmEntrance positionOutdoorsZones: I – II - IIIZone: ILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Tread surface (inlay):	Lux brushes recessed, robust
VersionOpen systemCodeNOBApprox. height (mm)24 mmEntrance positionOutdoorsZones: 1 - 11 - 111Zone: 1LoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:I.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Ideal for:	Coarse dirt
CodeNOBApprox. height (mm)24 mmEntrance positionOutdoorsZones: I - II - IIIZone: ILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Colors:	Black, Grey
Approx. height (mm)24 mmEntrance positionOutdoorsZones: I - II - IIIZone: ILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Version	Open system
Entrance positionOutdoorsZones: I - II - IIIZone: ILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Code	NOB
Zones: I - II - IIIZone: ILoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Approx. height (mm)	24 mm
LoadExtremeAutomatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Entrance position	Outdoors
Automatic door systemsProfile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Zones: I – II - III	Zone: I
accordance with EN 16005FootfallDaily footfall of 2000 and upRoll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Load	Extreme
Roll-over and drive-over capability:Wheelchairs, Prams, Hand and Light shopping trolleysSupport chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Automatic door systems	
Support chassisMade from rigid anodized aluminum with rubber sound insulation underlayAluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Footfall	Daily footfall of 2000 and up
Aluminum coating:Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Roll-over and drive-over capability:	Wheelchairs, Prams, Hand and Light shopping trolleys
aesthetically pleasing finish and harder surface than pure aluminum.Aluminum material thickness (mm)1.2ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Support chassis	Made from rigid anodized aluminum with rubber sound insulation underlay
ConnectionGalvanized steel cable and rubber spacersStandard profile clearance approx. (mm)5 mm (or 3mm for automatic/revolving doors)Slip resistanceR13Logo options:Logo engraving	Aluminum coating:	
Standard profile clearance approx. (mm) 5 mm (or 3mm for automatic/revolving doors) Slip resistance R13 Logo options: Logo engraving	Aluminum material thickness (mm)	1.2
Slip resistance R13 Logo options: Logo engraving	Connection	Galvanized steel cable and rubber spacers
Logo options: Logo engraving	Standard profile clearance approx. (mm)	5 mm (or 3mm for automatic/revolving doors)
	Slip resistance	R13
Contact STILMAT	Logo options:	Logo engraving
	Contact	STILMAT

Guarantee: 5 years on aluminum parts and construction