

# STILMAT KING

Carpet - open

**Code: NOC**

<b>Description:</b>	<b>Flexible and roll-up, aluminum entrance mat for laying on the floor. Custom produced mats to fit width and walking depth specifications perfectly. Suitable for wheeled traffic. Any geometric shape is available on demand.</b>
Model	KING (Carpet)
Tread surface (inlay):	High quality dust control carpet, durable and luxurious character. Made from 100% Polyamide
Ideal for:	Fine dirt and moisture
Colors:	Black, Grey, Brown...
Version	Open system
Code	NOC
Approx. height (mm)	20 mm
Entrance position	Indoors
Zones: I – II - III	Zone: III
Load	Extreme
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
Footfall	Daily footfall of 2000 and up
Roll-over and drive-over capability:	Wheelchairs, Prams, Hand and Light shopping trolleys
Support chassis	Made from rigid anodized aluminum with rubber sound insulation underlay
Aluminum coating:	Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.
Aluminum material thickness (mm)	1.2
Connection	Galvanized steel cable and rubber spacers
Standard profile clearance approx. (mm)	5 mm (or 3mm for automatic/revolving doors)
Slip resistance	DS
Logo options:	Logo engraving
Contact	STILMAT

Guarantee: 5 years on aluminum parts and construction